

# Kwaliteitshandboek Kolibri



Onderdeel:	Algemeen
Document:	DC05 Data specifications DTP E
Versie:	DC05/2.0/9 september 2025

## DATA SPECIFICATIONS DTP

	Flexo	Silkscreen	Offset
Minimum line thickness pos.	0,15 mm	0,15 mm	0,2 mm
Minimum line thickness neg.	0,2 mm	0,2 mm	0,3 mm
Grid	150 lpi - 62 p/cm <sup>2</sup>	64 lpi - 25 p/cm <sup>2</sup>	150 lpi - 62 p/cm <sup>2</sup>
Grid gradient	2% → 100%	n.v.t.	1% → 100%
Trapping	0,2 mm	0,2 mm	0,1 mm
Maximum # colors	7	9	6
Minimum corps size	4 pt	5 pt	4 pt
Minimum barcode scale	0,8	0,8	0,8
Total coverage	270%	270%	400%
Bleed	1 mm	1 mm	1 mm
Resolution	min 300 dpi	Vector	min 300 dpi
		Tactile min 1 mm line thickness	

	UV Inkjet/EFI	UV Inkjet/Canon
Minimum line thickness pos.	0,06 mm	0,06 mm
Minimum line thickness neg.	0,15 mm	0,1 mm
Grid		
Grid gradient	5% → 100%	0 → 100%
Trapping	X	X
Maximum # colors	FC + white	9 (4 flexo + 5 inkjet (FC+white))
Minimum corps size	3 pt	3 pt
Minimum barcode scale	0,86	0,8
Total coverage	340%	330%
Bleed	1 mm	1 mm
Resolution	360 x 360 dpi	min 300 dpi max 720 x 1080 dpi